

Buum® Standard Type III R - COARSE and FINE

- for all applications on a solid surface
- absorbs all kinds of liquids
- quick-acting
- excellent slip resistance



- **COARSE - grain size 0,5 - 4,0 mm**
particle sizes
 <0,125 mm 2,0 weight percentage
 0,125 - 0,5 mm 2,5 weight percentage
 0,5 – 4,0 mm 93,5 weight percentage
 >4,0 mm 2,0 weight percentage
- **bulk weight 465 g/ l**
absorption capacity, depending on liquid
ca.0,8 l per kg oil binder
- **sales unit 17-20 kg bag / approx. 44 l**
absorbs about 16 l / HEL
(test fluid extra light heating oil)
- **packaging unit CP1 pallet with 55 bags**

- **FINE - grain size 0,5 - 1,8 mm**
particle sizes
 <0,5 - 0,125 mm 2,3 weight percentage
 0,125 - 0,5 mm 1,8 weight percentage
 0,5 - 1,0 mm 80,3 weight percentage
 >1,0 -1,6 mm 15,6 weight percentage
- **bulk weight 520 g/ l**
absorption capacity, depending on liquid
ca.0,85 l per kg oil binder
- **sales unit 20 kg bag / approx. 40 l**
absorbs about 17 l / HEL
(test fluid extra light heating oil)
- **packaging unit CP1 pallet with 55 bags**