

Buum® Standard Type III R - COARSE and FINE

- for all applications on a solid surface
- absorbs all kinds of liquids
- quick-acting
- excellent slip resistance



• **COARSE - grain size 0,5 - 4,0 mm**

granular size in percent by weight

<0,125 mm	2,0 weight percentage
0,125 - 0,5 mm	2,5 weight percentage
0,5 - 4,0 mm	93,5 weight percentage
>4,0 mm	2,0 weight percentage

- **bulk weight 471 g/ l**
absorption capacity, depending on liquid
ca.0,8 l per kg oil binder
- **sales unit ca.14,5 kg bag / 30 l**
absorbs about 11,1 l / HEL
(test fluid extra light heating oil)
- **packaging unit CP1 pallet with 60 bags**

• **FINE - grain size 0,5 - 1,8 mm**

granular size in percent by weight

<0,5 - 0,125 mm	2,3 weight percentage
0,125 - 0,5 mm	1,8 weight percentage
0,5 - 1,0 mm	80,3 weight percentage
>1,0 -1,6 mm	15,6 weight percentage

- **bulk weight 507 g/ l**
absorption capacity, depending on liquid
ca.0,85 l per kg oil binder
- **sales unit ca. 16 kg bag / 30 l**
absorbs about 16,8 l / HEL
(test fluid extra light heating oil)
- **packaging unit CP1 pallet with 55 bags**